# Bauer massenza MI 6 Massenza M I 6 Water drill

## Allgemeine Merkmale

| | |
|---|---|
| **Marke** | Bauer |
| **Unterkategorie** | Bohranlage |
| **Baujahr** | 2005 |
| **Angezeigte Öffnungszeiten** | 3587 |
| **Farbe** | Gelb |
| **Zustand** | Gebraucht |
| **Allgemeiner Zustand** | Gut |
| **Kraftstoff** | Diesel |
| **Referenz** | BG361 |
| **CE-Kennzeichnung** | Ja |



## Eigenschaften

| | |
|---|---|
| **Ledig gewicht** | 9.900kg |

## Technische Spezifikationen

| | |
|---|---|
| **Vermögenswerte** | 156hp |

## Beschreibung

BG0236 Type: Drilling rig Brand: MASSENZA Model: MI.6 Engine: VM - 6 cylinder, liquid-cooled, 156 HP Hours on meter: 3852 Manufactured: 2005 Power 156 HP Dimensions L/H/W 7.00/2.80/2.40 MASSENZA HYDRAULIC DRILLING RIG MODEL MI6 mounted on TRACKS Used for water well research and geothermal applications. PARAMETERS: Strokes of rotary head/ feed length: 3760 mm Engine: VM - 6 cylinder, liquid-cooled, 156 HP PULL-DOWN SYSTEM: Hydraulically powered device by means of geared motor and heavy-duty high resistance chain. Hydraulically adjustable feed system of pull-down and hold back pressure on drill string. Pull-up max 56 kN (5,6 Tons) (12.346 lbs) Pull-down max 56 kN (5,6 Tons) (12.346 lbs) Chain strength in tension: 20.183 kg (44.496 lbs) Up-down adjustable handling fast feed rate from 0 to 35 m/min. SERVICE WINCH: Complete with 30 m of steel cable Ø 10 mm. Direct line pull 22 kN (4946 lbf) MASSENZA ROTARY HEAD model TM6.1: Internal diameter 50 mm (2"). Torque 6000 Nm - Speed 76 Rpm Torque 3000 Nm - Speed 152 Rpm MUD PUMP CAPRARI TWO STAGE ROTOR: Output flow max 1500 l/min Pressure max 16 bar STORAGE: For drill rods and casing pipes Rig is controlled by hydraulic levers !!! Weight: 9900KG